









Second-Generation Semi Active Öhlins Smart Electronic Control (S-EC)

Minimise cavitation, resulting in more stable damping control and improved bump absorption at high speeds.



Switchable ABS Modes

For flexible ability (and along with Rear Lift Control) the ABS gains two switchable modes: SPORT / TRACK.



Brembo Stylema Front **Brake Calipers**

The calipers maintain rigidity but are 7% lighter, with less internal fluid volume for more immediate reaction.



Titanium Muffler Developed Jointly with Akrapovic

It's made out of titanium for light weight, and the design also contributes to the bike's mass centralization.



Launch Control for Fast Starts

It limits engine rpm at 6,000, 7,000, 8,000 and 9,000 rpm set-points, even a wide-open throttle. A quickshifter is also fitted as standard.



Full-Color TFT Meter

Screen setting options with items like riding modes, speedometer and tachometer, shifter setting, ABS level and much more...





SPECIFICATIONS

| Engine Type | Liquid-Cooled, 4-Stroke, 16-Valve, DOHC, Inline-4 |
|---------------------|--|
| Displacement | 1,000 cm ³ |
| Bore x Stroke | 81.0 mm x 48.5 mm |
| Compression Ratio | 13.2 : 1 |
| Max. Power | 159.0 kW @ 14,500 rpm |
| Max. Torque | 112.7 N.m @ 12,500 rpm |
| Engine Oil Capacity | 4.0 € |
| Carburation | PGM-FI |
| TRANSMISSID | IN |
| Clutch Type | Wet Multiplate Hydraulic Clutch with Assist & Slipper Clutch |
| Transmission Type | 6-Speed Manual with Quickshifter, Mechanical (Chain drive |

| Dimensions (L x W x H) | 2,100 mm x 745 mm x 1,140 mm |
|------------------------|--|
| Wheelbase | 1,455 mm |
| Caster Angle | 24" |
| Trail | 102 mm |
| Seat Height | 830 mm |
| Ground Clearance | 115 mm |
| Kerb Weight | 201 kg |
| Fuel Tank Capacity | 16.1 (|
| SUSPENSION | 12 |
| Suspension Type | Front: 43mm Inverted Fork, Ohlins NPX Smart-EC with Preload, Compression and Rebound Adjustment |
| Suspension type | Rear: Prolink with Ohlins TTX36 Smart EC with Preload, Compression and Rebound Adjustment |

*Colours and photos may vary from the actual product.

| TOTAL PROPERTY AND ADDRESS OF THE PARTY AND AD |
|--|
| Rear: 17M/C x MT 6.00 |
| Front: 120/70-ZR17M/C 58W |
| Rear: 200/55-ZR17M/C 78W |
| Front: Dual Hydraulic Disc, Brembo STYLEMA8 4-Piston Calipers, ABS |
| Rear: Hydraulic Disc, Brembo 2-Piston Calipers, ABS |
| 7 |
| |
| |

Boon Siew Honda Sdn. Bhd.(676896-A)

721, Persiaran Cassia Selatan 1, Kawasan Perindustrian Batu Kawan. 14100 Simpang Ampat, Pulau Pinang.

HQ 04 506 3333 KL 03 6259 3516 / 03 6259 3517

JOHOR 07 244 8877 / 07 244 7557 TERENGGANU 09 624 0767 / 09 624 0746

All specifications are provisional and subject to change without notice.

- An specimations are provisional and subject to triangle windor trottee.
 Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, byre pressure, installatio of accessories, cargo, rider and passenger weight, and other factors.
- . Colours and photos may vary from the actual product. These models come with a 2 year or 20,000km manufacturing warranty (whichever comes first).

[Toll Free Line 1800 883993

Monday - Friday (9am - 5pm) Close on public holidays www.hondabigbike.com.my



Honda Motorcycle Malaysia hondamotorcycle.my

000

012-499 3991

AUTHORISED DEALER STAMP